



WMA Encoder

Product Data Sheet

v1.0

Updated: January 30, 2008

Features

- Supports Windows Media® Audio (WMA) audio encoding
- Compatible with up to WMA version 8
- Supports raw WMA and ASF formats output
- Supports the L1, L2 and L3 Profile
- Supports all WMA bit rates and sampling rates, as specified in the L1, L2 and L3 profiles
- Supports stereo and mono
- 16 bits PCM input
- Microsoft® platform certification
- GStreamer plugin wrapper for Linux® platforms
- DMO filter wrapper for Windows® CE platforms

Supported Platforms

- Hardware – i.MX ARM11™ platforms
- Software – eLinux, Windows® CE 5.0, Windows® Embedded CE 6.0 operating systems

Performance Metrics

i.MX35 eLinux Platforms

Typical Specifications: 48KHz, 128Kbps

Performance (MHz): 118.98

Memory Footprint (KB)

- ROM: 368.3
- RAM: 905.8

i.MX35 Windows® CE Platforms

Typical Specifications: 48 KHz, 128Kbps

Performance (MHz): 128.17

Memory Footprint (KB)

- ROM: 368.3
- RAM: 905.8

For further details, contact a Freescale customer representative.

Copyright © 2008 Freescale Semiconductor. All rights reserved.

Freescale Confidential and Proprietary