



PNG Decoder

Product Data Sheet

v1.0

Updated: Dec 11, 2008

Features

- Supports Portable Network Graphics (PNG) image decoding
- Supports PNG specification 1.0, zlib data format v 3.3 and deflate compressed data format v 1.3
- Supports PNG files that contain true-color image data (24 bits per pixel), grayscale mode, and indexed-color images of up to 256 colors
- Supports alpha transparency channel as well as transparency chunk handling
- Supports images encoded in interlaced order (Adams7 interlacing), as well as non-interlaced orders
- Supports RGB888, RGB565, RGB555, RGB666 and corresponding BGR format as output

Supported Platforms

- Hardware – i.MX ARM11™ platforms
- Software – eLinux, Windows® CE 5.0, Windows® Embedded CE 6.0 operating systems

Performance Metrics

i.MX31 eLinux Platforms

Typical Specifications: VGA (640 x 480)

Performance (MHz): 66.00

Memory Footprint (KB):

- ROM: 95
- RAM: 75.75

i.MX37 eLinux Platforms

Typical Specifications: VGA (640 x 480)

Performance (MHz): 66.00

Memory Footprint (KB):

- ROM: 95
- RAM: 75.75

i.MX31 Windows® CE Platforms

Typical Specifications: VGA (640 x 480)

Performance (MHz): 66.00

Memory Footprint (KB):

- ROM: 95
- RAM: 75.75

i.MX37 Windows® CE Platforms

Typical Specifications: VGA (640 x 480)

Performance (MHz): 66.00

Memory Footprint (KB):

- ROM: 95
- RAM: 75.75

For further details, contact a Freescale customer representative.